

officeUPS ups for PC

Features:

- 2 output sockets (French type)
- tower standalone,
- Modified sin output wave,
- Internal AGM battery,
- Automatic charger,
- LED display,
- AVR function



	Parametr	officeUPS-600	officeUPS-1200
ELECTRICAL	Input voltage	230Vac 50Hz	
	Input voltage range	165-290Vac 50Hz	
	Output Voltage range in mains mode	200-250Vac 50Hz	
	Output Voltage range in batterymode	230Vac 50Hz	
	Output waveform	Modified sine wave	
	Efficiency	>90% - mains mode >80% - battery mode	
	Output power	360W/600VA	720W/1200VA
	Transfer time	<10ms	
BATTERY	Battery	Internal (in set)	
	Capacity	12V 7Ah (1pcs)	12V 7Ah (2pcs)
	Battery type	VRLA AGM	
	Backup time	5min (300W)	5min (300W)
	Charger	Automatic charger	
ENVIRONMENT	Working temp.	0-40°C	
	Humidity	20-90%	
OTHER	Output sockets	2pcs (French type)	4pcs (French type)
	Dimmension	UPS: 314 / 97 / 143mm Box: 370 / 145 / 230mm	UPS: 350 / 120 / 188mm Box: 370 / 145 / 230mm
	Weight netto / brutto	4,5kg / 5kg (1pcs)	7kg / 7,5kg (1pcs)
	Packing	4pcs in full box	2pcs in full box
	Display LED	- mains mode (green) - battery mode (red) - overload (yellow)	
	EAN	 5 902135 125854	 5 902135 136676
PROTECTION	Overcurrent / Short circuit	Electronic fuse	